






Features

- 1/3 inch HPI Sensor
- High Resolution : 700TV Lines
- Built-in Fixed (f=3.6mm)
- TDN(ICR)
- Built-in IR LED(12EA), Smart IR
- Min Illumination : 0.00Lux (IR LED On)
- Auto White Balance
- 12VDC

DIMENSIONS



SPECIFICATIONS

Model	LRK-50S	LRK-51S
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency (H)	15.734 KHz	15.625 KHz
Scanning Frequency (V)	59.94 Hz	50 Hz
Image Sensor	1/3 Inch HPI Sensor	
Effective Pixels	976(H) x 496(V)	
Effective Window	960(H) x 480(V)	
Horizontal Resolution	700 TV Lines	
Video Output	CVBS: 1.0V p-p (75Ω, Composite)	
S/N Ratio	More than 47dB (AGC Off)	
Lens	Built-in Fixed Lens (f=3.6mm)	
Day & Night	TDN(ICR)	
IR LED and Sensor	Smart IR, IR LED 12EA (850nm, 45°)	
IR LED Visible Range	Max. 10m	
Min. Illumination	0.5 Lux (Color), 0.00 Lux (IR LED On)	
White Balance	Auto	
AGC	Auto	
Supplied Voltage	DC 12V (±20%)	
Power Consumption	Max. 1.32W/110mA	
Operating Temperature	-10℃ to +50℃	
Dimensions (WxHxD)	113.2 x 79.15 mm	
Weight	Approx. 190g	