

MN04/08/04P/08P



FEATURES

- H.264 / MPEG4 / JPEG
- Recording Mode:
1080P(1920*1080) / 720P(1280*720) / D1(704*480)
- Manage Video & Audio from IP Camera incl.
- Max. 4/8CH Decoding & Display
- Auto Searching & Setting IP Camera in LAN
- Network Access up to 20 users
- Max. 1 SATA HDD up to 3TB & USB External Device
- 1 HDMI, 1 VGA & 4/1 Audio
- 2 Sensor / 1 Alarm out
- Easy Control : Remote controller / Mouse
- Client Viewer, CMS & Mobile Viewer, Free DDNS server

SPECIFICATIONS

	MN04/08	MN04P/08P (PoE)
System Resources	4/8-channel series product support 4/8-channel HD connection respectively. Max supports 80Mbps.	
Operation System	Embedded Linux real-time operation system	
Operation Interface	WEB/Local GUI	
Video Compression	H.264	
Decode Capacity	Max supports 80Mbps, supports 3M&5M decode	
Audio Compression	G.711a, G.726	
Video Output	1-channel VGA analog video output.	
Video Input	4/8-ch network compression video input	
HDMI	1-ch HDMI output.	
Audio Input	1-ch bidirectional talk input	
Audio Output	1-ch bidirectional talk output	
Window Split	1/4/9-window	
Multiple-channel Playback	Max 4-channel 1080P playback.	
Alarm Input	2-ch alarm input	
Alarm Output	1-ch alarm output	
Storage	1 built-in SATA ports.	
USB Port	USB2.0 x 1, USB3.0 x 1	
Network Connection	One RJ45 10/100/1000Mbps Ethernet port.	
Power Port	Input DC 12V.	Input DC 48V.
Power On-off Button	One button. At the front-panel.	
IR Receiver Window	Support IR remote control	
Clock	Built-in clock.	
Indication Light	One power status indicator light.	
	One network status indicator light.	
	One HDD status indicator light.	
Power Consumption	< 15W (Exclude HDD)	
Working Temperature	-10℃ ~ +55℃	
Working Humidity	10% ~ 90%	
Air pressure	86kpa ~ 106kpa	
Dimension	325mm × 240mm × 45mm	325mm × 240mm × 45mm
Weight	1.5KG (Exclude HDD)	
Installation	Desk installation	